

American Building Restoration Products, Inc.

Restoring the Old, Preserving the New.



EST. 1970

ABR Fast Finish Remover[®]

Removes oil and water based stains.

FR001

DANGER!

Keep out of the reach of children.

WARNING: Harmful or fatal if swallowed.

Will cause burns to the skin.

Read carefully other cautions on side panel.

1 U.S. GALLON
(3.785 Liters)

KEEP OUT OF THE REACH OF CHILDREN

THIS PRODUCT SHOULD BE USED BY EXPERIENCED CONTRACTORS. FOR PROFESSIONAL USE ONLY.

CHECK WITH SPRAY EQUIPMENT MANUFACTURER FOR CHEMICAL COMPATIBILITY WITH ABR FAST FINISH REMOVER®.

ABR Fast Finish Remover® is an economical, concentrated, water soluble remover of stains, latex paints, varnishes and other coatings from all types of surfaces, including wood, masonry and metal. Surfaces treated with **ABR Fast Finish Remover®** must be neutralized with **X-180 Weathered Wood Restorer™**.

INSTALLATION

PREPARATORY WORK: Surface should be free of heavy dirt and debris. **NOTE:** Before beginning overall project, test to determine dwell time and most effective application procedure required to produce desired results. User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. Follow all local, state, or federal disposal regulations when using this product. Protect all adjacent surfaces including plants and shrubbery. Beware of wind drift onto auto and pedestrian traffic when rinsing or applying **ABR Fast Finish Remover®**. Have cold running water available at the project site at all times to flush **ABR Fast Finish Remover®** if needed to avoid injury and/or property damage.

APPLICATION

1. For most projects, dilute 4 parts water to 1 part **ABR Fast Finish Remover®**. For more difficult jobs use a stronger dilution or full strength. Dilution ratio should be determined by testing before beginning project.
2. Using a synthetic brush, roller, low pressure sprayer (not to exceed 100 PSI) or a hand pump sprayer (45 PSI) apply a thick coat of **ABR Fast Finish Remover®** to surface. Do not use any high pressure airless sprayer as dangerous atomization will occur.
- CAUTION:** **ABR Fast Finish Remover®** is slippery when applied to horizontal surfaces. Use extreme caution when working on horizontal walking surfaces.
3. Let **ABR Fast Finish Remover®** remain on the surface until finish has softened. Wait for the entire surface to become uniformly darkened. This darkened appearance indicates **ABR Fast Finish Remover®** has dissolved the underlying finish and is ready to be rinsed.
4. If **ABR Fast Finish Remover®** has to remain on surface for 30 minutes or longer it may dry prematurely. In this instance, moisten dry areas by applying a 50/50 water/**ABR Fast Finish Remover®** mix. Then mist this surface with a fine water spray. A reapplication may be necessary for overhangs, corners, windows and the like where **ABR Fast Finish Remover®** tends to move downward.

Coverage: 50-100 square feet per gallon depending on the composition of the finish, the number of layers to strip and the dilution with water.

REMOVAL

1. Scrape or vacuum all dissolved residue and discard in an appropriate container. Follow this procedure with a water rinse (hot water works best) ranging from garden hose pressure (which may require scrubbing) to a high pressure water rinse. On wood, adjust pressure to 600 psi or lower to avoid damage to wood fiber. Waiting to remove **ABR Fast Finish Remover®** requires more rinse time.
2. Certain types of wood surfaces may have a raised grain effect after stripping is completed. Sanding may be required to smooth out this condition.
3. Neutralize the surface with **X-180 Weathered Wood Restorer™** (see product label and specification sheet for instructions).

IMPORTANT: The stripping process may darken some woods. This darkening can be removed with the required follow-up neutralization with **X-180 Weathered Wood Restorer™**.

CLEAN UP

Water flush equipment, shrubbery, sidewalks, blacktop, asphalt, and other adjacent surfaces immediately upon contact. Leave job site free of any trace amounts of **ABR Fast Finish Remover®** or dissolved residue. Never leave behind any containers or equipment. Appropriately label containers of residue for proper disposal.

FIRST AID

INHALATION: SEVERE IRRITANT. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. **Call a physician.**

INGESTION: TOXIC. If swallowed, **DO NOT INDUCE VOMITING.** Give large quantities of water or milk. Never give anything by mouth to an unconscious person. **GET MEDICAL ATTENTION IMMEDIATELY.**

SKIN CONTACT: CORROSIVE. Immediately flush thoroughly with cool water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Discard non-rubber shoes. **GET MEDICAL ATTENTION IMMEDIATELY.**

EYE CONTACT: HIGHLY CORROSIVE! Immediately flush eyes with plenty of cool water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation. **GET MEDICAL ATTENTION IMMEDIATELY.**

READ MATERIAL SAFETY DATA SHEET AND DIRECTIONS BEFORE USING THIS PRODUCT.

THIS PRODUCT MAY CAUSE BURNS, WHICH MAY NOT BE IMMEDIATELY PAINFUL OR VISIBLE, AND IS HARMFUL OR FATAL IF SWALLOWED.

FOLLOW FIRST AID INSTRUCTIONS AND CALL PHYSICIAN IMMEDIATELY IN CASE OF CONTACT OR SUSPICION OF CONTACT.

FOR CHEMICAL EMERGENCY ONLY, CALL CHEMTREC AT 1-800-424-9300. FOR ALL OTHER INQUIRIES ABOUT THIS PRODUCT, CALL 1-800-346-7532.

WILL CAUSE PERMANENT BLINDNESS IF EYE CONTACT OCCURS. PROTECT EYES WITH CHEMICAL SPLASH PROOF GOGGLES AND FULL FACE SHIELD.

POTASSIUM HYDROXIDE SOLUTION
8 UN1814 PG II



0 98957 90001 6

BATCH NO. _____

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from **ABRP, Inc.**, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering **ABRP, Inc.**'s obligation under this warranty. Read and follow label directions and observe all safety precautions in the use of this product.

ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced.

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS.

NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, **ABRP, INC.'S** LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state.

ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

For more information on the specialty line of products offered by **ABRP, Inc.** please contact one of our technical representatives at 800-346-7532 or visit our web site at abrp.com

Manufactured by:



American Building Restoration Products, Inc.

9720 South 60th Street, Franklin, Wisconsin 53132
414-421-4125 • Fax: 414-421-8696 • 1-800-346-7532 • email: abrp@abrp.com

Copyright © 2010 American Building Restoration Products, Inc. XX-10/XXM